


JJT1 MÓDULO RECTO 1 m
STRAIGHT PIPE 1 m


Øint	80	100	130
Øext	125	150	200
L útil	942	942	942
A	50	50	50


JJTO MÓDULO RECTO 0,5 m
STRAIGHT PIPE 0,5 m


Øint	80	100	130
Øext	125	150	200
L útil	442	442	442


JJTP MÓDULO RECTO 0,25 m
STRAIGHT PIPE 0,25 m


Øint	80	100	130
Øext	125	150	200
L útil	192	192	192


JJEG MÓDULO EXTENSIBLE 0,35 A 0,52 m
ADJUSTABLE PIPE 0,35 TO 0,52 m


Øint	80	100	130
Øext	125	150	200
L min	350	350	350
L max	520	520	520


JJES MÓDULO EXTENSIBLE 0,52 A 0,88 m
ADJUSTABLE PIPE 0,52 TO 0,88 m


Øint	80	100	130
Øext	125	150	200
L min	520	520	520
L max	880	880	880


JJMC MÓDULO DE COMPROBACIÓN 0,5 m
CHECKING LENGTH 0,5 m


Øint	80	100	130
Øext	125	150	200
L útil	442	442	442


JJCC CODO DE 45°
ELBOW 45°


Øint	80	100	130
Øext	125	150	200
X	66	70	77
Y	115	123	141


JJCN CODO DE 90°
ELBOW 90°


Øint	80	100	130
Øext	125	150	200
X	163	175	200
Y	115	127	152




JJTN	TE 90°		
	TEE 90°		
Øint	80	100	130
Øext	125	150	200
L útil	325	350	400
B	133	145	170
C	80	92	117




JJTB	TE COAXIAL HUMOS HEMBRA		
	TEE COAXIAL FLUE FEMALE BRANCH		
Øint	80	100	130
Øext	125	150	200
L útil	192	212	242
ØA	80	100	130
B	120	130	150
C	143	156	180



JJTE	TE COAXIAL HUMOS HEMBRA		
	TEE COAXIAL FLUE FEMALE BRANCH		
Øint	80	100	130
Øext	125	150	200
L útil	-	192	-
B	-	120	-
C	-	156	-




JJTD	TE COAXIAL HUMOS MACHO		
	TEE COAXIAL FLUE MALE BRANCH		
Øint	80	100	130
Øext	125	150	200
L útil	192	212	-
ØA	80	100	-
B	120	130	-
C	93	105	-




JJTC	TE COAXIAL ENTRADA AIRE		
	TEE COAXIAL AIR ENTRY		
Øint	80	100	130
Øext	125	150	200
L útil	192	192	192
B	120	120	120
C	114	126	151




JJTA	TAPA COAXIAL		
	LID		
Øint	80	100	130
Øext	125	150	200
B	70	70	70




JJTV	TERMINAL SALIDA VERTICAL 1 m		
	PIPE WITH VERTICAL OUTSIDE 1 m		
Øint	80	100	130
Øext	125	150	200
L útil	930	930	930




JJTX	TERMINAL SALIDA VERTICAL 0,28 m		
	PIPE WITH VERTICAL OUTSIDE 0,28 m		
Øint	80	100	130
Øext	125	150	200
L útil	360	390	420


JJTH **TERMINAL SALIDA HORIZONTAL 1 m**
PIPE WITH HORIZONTAL OUTSIDE 1 m


Øint	80	100	130
Øext	125	150	200
L útil	940	940	940
B	795	765	705


JJHE **TERMINAL SALIDA HORIZONTAL EXTENSIBLE**
HORIZONTAL TERMINAL ADJUSTABLE


Øint	80	100	130
Øext	125	150	200
A min	670	670	670
A max	915	916	915
B min	477	459	433
B max	721	705	678


JJAM **AMPLIACIÓN**
INCREASER


ØA	80/125	100/150	-
ØB	100/150	130/200	-
L útil	177	177	-


JJRE **REDUCCIÓN**
REDUCER


ØA	100/150	130/200	-
ØB	80/125	100/150	-
L útil	177	177	-


JJSB **SOPORTE BASE REGULABLE 50 A 80 mm**
ADJUSTABLE BASE SUPPORT 50 TO 80 mm


Øint	80	100	130
Øext	125	150	200
L útil	195	195	195
Bmin.	50	50	50
Bmax.	80	80	80


JJMQ **MÓDULO 0,10 m CON PLACA**
PIPE 0,10 m WITH PLATE


Øint	80	100	130
Øext	125	150	200
L útil	100	100	100
D	420	420	420
E	520	520	520


HISB **SOPORTE BASE REGULABLE 0 A 120 mm**
BASE SUPPORT 0 TO 120 mm


Ønom	125	150	200
L	154	130	184
J	170	195	245
Bmin.	0	0	0
Bmax.	120	120	120


HISA **SOPORTE MURAL REGULABLE 50 A 80 mm**
ADJUSTABLE WALL SUPPORT 50 TO 80 mm


Ønom	125	150	200
Amin.	50	50	50
Amax.	80	80	80
B	30	30	40


HIS1 **SOPORTE MURAL REGULABLE 80 A 130 mm**
ADJUSTABLE WALL SUPPORT 80 TO 130 mm


\varnothing_{nom}	125	150	200
Amin.	80	80	80
Amax.	130	130	130
B	30	30	40


HIS2 **SOPORTE MURAL REGULABLE 130 A 210 mm**
ADJUSTABLE WALL SUPPORT 130 TO 210 mm


\varnothing_{nom}	125	150	200
Amin.	130	130	130
Amax.	210	210	210
B	30	30	40


HISF **SOPORTE FORJADO**
JOIST SUPPORT


\varnothing_{nom}	125	150	200
A	150	150	150
B	30	30	40


HIST **SOPORTE DE TEJADO**
ROOF SUPPORT


\varnothing_{nom}	125	150	200
A	150	150	150
B	30	30	40


HISV **SOPORTE DE TEJADO REFORZADO**
REINFORCED ROOF SUPPORT


\varnothing_{nom}	125	150	200
A	637	662	712
B	80	80	80
C	150	150	150


HISS **SOPORTE SUELO**
FLOOR SUPPORT


\varnothing_{nom}	125	150	200
A	88	100	125
B	30	30	40
Hmin.	80	80	80
Hmax.	300	300	300


HISN **SOPORTE 1 m PARA ESTRUCTURA MADERA**
WOODEN SUPPORT 1 m


\varnothing_{nom}	125	150	200
\varnothing_A	125	150	200
B	1000	1000	1000


HGSC **PLACA PARA SOPORTE ESTRUCTURA MADERA**
PLATE FOR SUPPORT FOR WOODEN JOIST


\varnothing_{nom}	125	150	200
A	131	156	181


HICI **COQUILLA PASO FORJADOS ESPESOR 100 mm**
INSULATED ROOF SLEEVE 100 mm THICKNESS


\varnothing_{nom}	125	150	200
\varnothing_A	325	350	400
B	400	400	400


HIPN TAPAJUNTAS INOX. REDONDO
ROUND INOX ROSETTE


Ønom	125	150	200
A	120	120	120
Øext	374	399	450


HITJ TAPAJUNTAS
WALL ROSETTE


Ønom	125	150	200
A	40	40	40
B	15	15	15


HIPE PLACA EMBELLECEDORA CUADRADA DE 0-30°
SQUARE FINISHING PLATE 0-30°


Ønom	125	150	200
A	128	153	203
B	308	333	440
C	90	90	90


HIPB PLACA EMBELLECEDORA CUADRADA DE 30°- 45°
SQUARE FINISHING PLATE 30°- 45°


Ønom	125	150	200
A	128	153	203
B	308	333	440
C	90	90	90


HIAV ABRAZADERA DE VIENTOS
ANTI-WIND LOCKING BAND


Ønom	125	150	200
B	30	30	40


HICU CUBREAGUAS ADAPTABLE 0 A 35°
ADJUSTABLE FLASHING 0 TO 35°


Ønom	125	150	200
A	610	640	700
B	150	175	225
C	150	160	180


HICR CUBREAGUAS PLOMO 0 - 20°
LEAD FLASHING 0 - 20°


Ønom	125	150	200
A	671	697	750
B	650	675	725
C	135	160	210


HICS CUBREAGUAS PLOMO 20°- 45°
LEAD FLASHING 20°- 45°

Ønom	125	150	200
A	751	786	855
B	650	675	725
C	135	160	210


HICT CUBREAGUAS PLOMO 45°-60°
LEAD FLASHING 45°- 60°


\varnothing nom	125	150	200
A	805	855	953
B	650	675	725
C	135	160	210


HILL COLLARÍN ANTILLUVIA
STORM COLLAR


\varnothing nom	125	150	200
\varnothing ext	200	225	300
\varnothing int	125	151	201
A	75	75	100


HILM COLLARÍN ANTILLUVIA CORTO
SHORT STORM COLLAR


\varnothing nom	125	150	200
\varnothing ext	251	276	326
\varnothing int	126	151	201
A	32	32	32


JJAD ADAPTADOR A CALDERA
BOILER ADAPTOR


\varnothing A	80/125	100/150	130/200
\varnothing B	80/125	100/150	130/200
L útil	145	145	145


JJMD ADAPTADOR A CALDERA MACHO
MALE BOILER ADAPTOR

\varnothing A	80/125	100/150	130/200
\varnothing B	80/125	100/150	130/200
L útil	60	60	60


JJTM ADAPTADOR BJ A JJ CON ENTRADA DE AIRE Ø60
ADAPTOR BJ TO JJ WITH Ø60 AIR ENTRY

\varnothing int	80	100	130
\varnothing BJ	80	100	130
L útil	179	-	-
B	105	-	-
C	113	-	-


JJBI ADAPTADOR BI A JJ
ADAPTOR BI TO JJ

\varnothing int	80	100
\varnothing BI	80	100
L útil	107	107